



BULLETIN # 03T-2

Carlyle/RCD Refrigeration Products
PO Box 4808
Carrier Parkway, TR3
Syracuse, NY 13221

SUBJECT

DATE: January 17, 2003 (Revised March 28, 2006)
AUTHOR: Paul Tollar

PRODUCT SERVICE & PARTS GENERAL

Product Name: 06E, 06CC, 06T

DESCRIPTION

This bulletin is to update and replace Carlyle Bulletin 00T-6 dated July 7, 2000. The only significant change in this bulletin from the earlier data is there is a new circuit breaker selection for the 30 Hp for 400/460v applications for the 06E & 06TA compressors. The older HH83XA425 circuit breaker has been discontinued and replaced by the HH83XA478 circuit breaker. Slight changes were made in the calibration settings to assist in avoiding nuisance trips.

The attached tables detail these recommendations. Circuit breaker part numbers that are followed by an asterisk indicate that the circuit breaker requires "ring" type power wire terminals. All other circuit breakers listed in these tables utilize a "compression" type power wire terminal.

Many of our 460-volt models have recommendations for both the larger body (XA), and the smaller body (XB), circuit breakers. This allows the customer to choose the most practical or economical circuit breaker for their application.

To assure availability of these circuit breakers, we have increased our minimum inventory levels for the 'Recommended Circuit Breaker' for each model. The 'Alternate' circuit breaker shown in these tables may have a six-week lead-time.



BULLETIN # 03T-2

Carlyle/RCD Refrigeration Products
 PO Box 4808
 Carrier Parkway, TR3
 Syracuse, NY 13221

COMPRESSOR INFORMATION					RECOMMENDED CIRCUIT BREAKERS							
06ER MODELS	VOLTAGE	HP	MAX. M.T.A.	LRA XL	RECOMMENDED PART #	MUST HOLD AMPS	M.T.A.	LRA	ALTERNATE PART #	MUST HOLD AMPS	M.T.A.	LRA
06ER450100	575	15	38	96	HH83XA460	29	33.5	97	HH83XB634	28	33	96
450600	400/460		46	142	HH83XA463	40	46	150	HH83XB695	40	46	142
450300	208/230		90	283	HH83XB626	78	90	250	HH83XB356*	78	90	250
450300	460		46	142	HH83XA463	40	46	150	HH83XB695	40	46	142
06ER465100	575	20	45	120	HH83XA461	33	38	124	HH83XB422	34	40	120
465600	400/460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
465300	208/230		108	345	HH83XB625	91	104	350	HH83XB336*	91	104	350
465300	460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
06ER475100	575	20	45	120	HH83XA461	33	38	124	HH83XB422	34	40	120
475600	400/460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
475300	208/230		108	345	HH83XB625	91	104	350	HH83XB336*	91	104	350
475300	460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
06ER399100	575	30	65	176	HH83XA430	50	56	168	HH83XB683	54	62	172
399600	400/460		84	253	HH83XA478	65	76	274	HH83XB609	67	76	274
399300	208/230		168	506	HH83XC539	142	163	507				
399300	460		84	253	HH83XA478	65	76	274	HH83XB609	67	76	274

COMPRESSOR INFORMATION					RECOMMENDED CIRCUIT BREAKERS							
06EM MODELS	VOLTAGE	HP	MAX. M.T.A.	LRA XL	RECOMMENDED PART #	MUST HOLD AMPS	M.T.A.	LRA	ALTERNATE PART #	MUST HOLD AMPS	M.T.A.	LRA
06EM450100	575	15	38	96	HH83XA460	29	33.5	97	HH83XB634	28	33	96
450600	400/460		46	142	HH83XA463	40	46	150	HH83XB695	40	46	142
450300	208/230		90	283	HH83XB626	78	90	250	HH83XB356*	78	90	250
450300	460		46	142	HH83XA463	40	46	150	HH83XB695	40	46	142
06EA565100	575	25	57	164	HH83XA469	46	53	164	HH83XB615	45	51	172
565600	400/460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
565300	208/230		140	446	HH83XC509	110	127	420	HH83XC571	112	128	433
565300	460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
06EM475100	575	25	57	164	HH83XA469	46	53	164	HH83XB615	45	51	172
475600	400/460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
475300	208/230		140	446	HH83XC509	110	127	420	HH83XC571	112	128	433
475300	460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
06EM499100	575	35	77	212	HH83XA453	68	78	236	HH83XB680	63	73	240
499600	400/460		96	305	HH83XA547	77	88	283	HH83XB648	75	87	280
499300	208/230		193	610	HH83XC532	158	182	590				
499300	460		96	305	HH83XA547	77	88	283	HH83XB648	75	87	280



BULLETIN # 03T-2

Carlyle/RCD Refrigeration Products
 PO Box 4808
 Carrier Parkway, TR3
 Syracuse, NY 13221

COMPRESSOR INFORMATION					RECOMMENDED CIRCUIT BREAKERS							
08EA MODELS	VOLTAGE	HP	MAX. M.T.A.	LRA XL	RECOMMENDED PART #	MUST HOLD AMPS	M.T.A.	LRA	ALTERNATE PART #	MUST HOLD AMPS	M.T.A.	LRA
08EA550100	575	20	45	120	HH83XA461	33	38	124	HH83XB422	34	40	120
550600	400/460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
550300	208/230		108	345	HH83XB625	91	104	350	HH83XB336*	91	104	350
550300	460		54	173	HH83XA424	42	49	175	HH83XB606	43	49	173
08EA585100	575	25	57	164	HH83XA469	46	53	164	HH83XB815	45	51	172
585600	400/460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
585300	208/230		140	446	HH83XC509	110	127	420	HH83XC571	112	128	433
585300	460		70	223	HH83XA426	55	64	210	HH83XB607	56	64	215
06EA575100	575	30	65	176	HH83XA430	50	58	168	HH83XB683	54	62	172
575600	400/460		84	253	HH83XA478	65	78	274	HH83XB609	67	76	274
575300	208/230		168	508	HH83XC539	142	163	507				
575300	460		84	253	HH83XA478	65	76	274	HH83XB609	67	76	274
06EA599100	575	40	94	276	HH83XA551	74	86	236	HH83XB636	77	89	240
599600	400/460		118	345	HH83XA550	92	106	295	HH83XB405*	88	102	300
599300	208/230		236	690	HH83XC537	187	215	636				
599300	460		118	345	HH83XA550	92	106	295	HH83XB405*	88	102	300

COMPRESSOR INFORMATION					RECOMMENDED CIRCUIT BREAKERS							
06CC MODELS	VOLTAGE	HP	MAX. M.T.A.	LRA XL	RECOMMENDED PART #	MUST HOLD AMPS	M.T.A.	LRA	ALTERNATE PART #	MUST HOLD AMPS	M.T.A.	LRA
06CC550J	575	15	27	98	HH83XB438*	23	27	86	HH83XB689	23	27	86
06CC550F	400/460		32	142	HH83XB414*	27	32	145	HH83XB698	27	32	145
06CC550E	208/230		68	283	HH83XB455*	59	68	245	HH83XB697	59	68	245
06CC550E	460		32	142	HH83XB414*	27	32	145	HH83XB698	27	32	145
06CC665J	575	20	38	120	HH83XA461	33	38	124				
06CC665F	400/460		50	173	HH83XB437*	43	50	176	HH83XB606	43	49	173
06CC665E	208/230		100	345	HH83XB376*	73	85	333				
06CC665E	460		50	173	HH83XB437*	43	50	176	HH83XB606	43	49	173
06CC675J	575	20	38	120	HH83XA461	33	38	124				
06CC675F	400/460		50	173	HH83XB437*	43	50	176	HH83XB606	43	49	173
06CC675E	208/230		100	345	HH83XB378*	77	89	365				
06CC675E	460		50	173	HH83XB437*	43	50	176	HH83XB606	43	49	173
06CC899J	575	30	58	176	HH83XA430	50	58	168	HH83XA469	46	53	164
06CC899F	400/460		73	253	HH83XB432*	63	73	240	HH83XB604	63	73	240
06CC899E	208/230		141	506	HH83XC406	122	141	464				
06CC899E	460		73	253	HH83XB432*	63	73	240	HH83XB604	63	73	240